



## MATEX PRO

Interior Emulsion

### Recommended Uses

You can utilize Matex Pro for decoration and protection of interior walls, ceilings, plaster, brickwork, and wall boards.

### Composition

- Pigments** : Mainly contain Titanium Dioxide, Iron Oxide, Organic Pigments, and Mineral Extender.
- Binder** : Acrylic Copolymer Emulsion.
- Thinner** : Clean Water

### Application Methods

Thinning by Volume

- 1) Brush** : Dilute the paint with 50-70% water
- 2) Roller** : Dilute the paint with 20-30% water
- 3) Conventional Air Spray** : Dilute the paint with 30-40% water

### Product Description

Nippon Matex Pro is an acrylic based emulsion designed for interior concrete surfaces including walls and ceilings. It gives your walls a good hiding and covering. This paint is specially designed for projects and for those areas where high demands of scrub and smoothness are not prime requirements.



- Clean Up :** Clean up equipment with water immediately after use.
- Note :** Do not keep diluted paint for more than 1 day. If kept for longer periods it can lead to paint infection, color change and loss of viscosity.

## Surface Preparation

For Bare masonry surfaces make sure it should be completely dry and free from dust, dirt, and grease. Sand and dust off your walls thoroughly.

## Previously Painted Surfaces

**Sound Surface:** Make your surface sound by removing unstable paint film, and lose chalk by rubbing it down with abrasive paper or wire brush and dusting it off. Prime your walls with NIPPON VINILEX 5100 wall sealer. You can fill your wall's surface with NIPPON PUTTY if necessary.

**Severely Defected Surface:** If your walls have large cracks and holes use a sand and cement mixture and allow them to dry thoroughly drying. Prime your walls with NIPPON VINILEX 5100 primer and fill them with NIPPON PUTTY. Scuff to make your walls smooth and dust off.



## Recommended Paint System

**Type of Substrate:**  
FOR MASONRY

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON ACS PUTTY	2-3	
Finish	NIPPON MATEX PRO	3-4	
Note:	It can be applied directly to ceilings where the coating is a major factor.		

**Standard Packing** : Ready Mix: 24 kg

## Safety, Health and Environmental Information

Keep the paint out of reach of children and away from eatable items. Wear a mask and protective clothing while applying the paint. Do not discharge into drains or in an open environment.

Our paint is free of Lead, Mercury, Chromium, and Cadmium compounds.

## Note

### Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control many conditions under which our products may be used, we can only guarantee the quality of the product.