



NIPPON EASY COAT EMULSION (Interior Emulsion)

Recommended Uses

You can use Nippon Easy Coat Emulsion For decoration and protection of interior walls, ceilings, plaster, brickwork, and wall boards.

Composition

- Pigments** : It mainly Titanium Dioxide, Iron Oxide, Organic Pigments and Mineral Extender.
- Binder** : Vinyl Acrylic Copolymer Emulsion.
- Thinner** : Clean Water

Application Methods

Thinning by Volume

- 1) Brush** : Dilute the paint with 50-70% water
- 2) Roller** : Dilute the paint with 20-30% water
- 3) Conventional Air Spray** : Dilute the paint with 30-40% water

Product Description

Nippon Easy Coat is an economical emulsion specially formulated for the decoration and protection of interior walls, ceilings, brickwork, hard, and soft boards, and asbestos. With good brushing and leveling properties, it's a combination of cool and vibrant colors. Nippon Easy Coat stands out to be the best economical choice for its users.



Clean Up : Clean up your equipment with water immediately after use.

Surface Preparation

For bare masonry surfaces make sure your walls should be completely dry and free from dust, dirt, and grease. Sand and dust off your walls thoroughly. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are high.

(Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

Previously Painted Surfaces

Sound Surface:

Make your wall's surface sound by removing unstable paint film, and lose chalk by rubbing down using abrasive paper or wire brush and dusting off. Prime your walls with NIPPON VINILEX 5100 WALL SEALER. Fill the surface of your walls with NIPPON ACS PUTTY if necessary.

Severely Defected Surface:

In case your walls have large cracks use a sand and cement mixture to repair them and allow them to thorough drying. Prime your walls with NIPPON VINILEX 5100 WALL SEALER and fill them with NIPPON ACS PUTTY. Scuff to make your walls smooth and dust off.



Recommended Paint System

Type of Substrate:
FOR MASONRY

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON ACS PUTTY	2-3	
Finish	NIPPON EASYCOAT EMULSION	3-4	

Standard Packing : 3.64L, 14.56L

Safety, Health and Environmental Information

Keep the paint out of reach of children and away from eatable items. Wear a mask and protective clothing while applying the paint. Do not discharge into drains or in an open environment.

Our paint is free of Lead, Mercury, Chromium, and Cadmium compounds.

Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control many conditions under which our products may be used, we can only guarantee the quality of the product.