



## NIPPON EASY WASH

Interior Paint

### Recommended Uses

You can utilize Matex Pro for decoration and protection of interior walls, ceilings, plaster, brickwork, and wall boards.

### Composition

**Pigments** : Mainly contain Titanium Dioxide, Iron Oxide, Organic Pigments, and Mineral Extender.

**Binder** : Acrylic Polymer

**Thinner** : Clean Water

### Application Methods

#### TOOL

- 1) **Brush** : Thinning by Volume : Dilute the paint with 50-70% water
- 2) **Roller** : Dilute the paint with 20-30% water
- 3) **Conventional Air Spray** : Dilute the paint with 30-40% water

### Product Description

Nippon Easy wash is a premium quality water based matt formulated on specialized Acrylic binder modified with silicone additives and specially designed to give a luxurious smooth silky finish to interior masonry surfaces, brickworks & wallboards. It is a highly washable emulsion with added fresh lemon fragrance. Its fungus resistance, smooth silky finish properties, and long-lasting colors make it an ideal choice for interiors.



## Surface Preparation

### Bare Masonry

For Bare Masonry surfaces make sure your walls should be completely dry and free from dust, dirt, and grease. Apply NIPPON VINILEX 5100 WALL SEALER and allow it to dry thoroughly. Sand and dust off your walls and make them smooth by applying 2-3 coats of NIPPON ACS PUTTY. Avoid painting when the moisture content and alkalinity of the walls are high.

(Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

## Previously Painted Surfaces

### Sound Surface:

Make your surface sound by removing unstable paint film, and lose chalk by rubbing down using abrasive paper or wire brush and dusting off. Prime your walls with NIPPON VINILEX 5100 WALL SEALER. You can fill the surface of your walls with NIPPON ACS PUTTY if necessary.

### Severely Defected Surface:

Masonry work is recommended to repair large cracks and holes. Allow drying thoroughly. Prime your walls with NIPPON VINILEX 5100 WALL SEALER and fill with NIPPON ACS PUTTY. Scuff to make it smooth and dust it off.



## Recommended Paint System

**Type of Substrate:**  
FOR MASONRY

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON ACS PUTTY	2-3	
Finish	NIPPON EASY WASH	3-4	

**Standard Packing** : 1L, 4L & 16 L

## Safety, Health and Environmental Information

Keep the paint out of reach of children and away from eatable items. Wear a mask and protective clothing while applying the paint. Do not discharge into drains or in an open environment.

Our paint is free of Lead, Mercury, Chromium, and Cadmium compounds.

## Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control many conditions under which our products may be used, we can only guarantee the quality of the product.