

NIPPON MATEX GOLD

Interior Emulsion

Recommended Uses

It is highly recommended For decoration and protection of interior walls, ceilings, plaster, brickwork, hard and soft boards, and asbestos.

Composition

Pigments	:	Mainly contain Titanium Dioxide Iron Oxide, Organic Pigments, and Mineral Extender.	
Binder Thinner	•	PVA Clean Water	

Application Methods

Thinning by Volume

- 1) Brush
- 2) Roller
- 2) Conventional Air Spray
- : Dilute the paint with 50-70% water
- : Dilute the paint with 20-30% water
- : Dilute the paint with 30-40% water



Product Description

Nippon Matex Gold has been formulated to enhance the beauty of interior walls with good washability. Nippon Matex Gold offers the freedom to choose from a broad spectrum of colours for every mood.

Clean Up : Clean up your equipment with water immediately after use.

Surface Preparation

Bare masonry surfaces should be completely dry and free from dust, dirt and grease. Use Bleach solution to treat the surface affected by fungus. Apply NIPPON VINILEX 5100 WALL SEALER and allow it to dry completely. Avoid painting when the moisture content and alkalinity of the walls are high.

(Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

Previously Painted Surfaces

Sound Surface: Make your surface sound by removing unstable paint film, and lose chalk by rubbing down using abrasive paper or wire brush and dusting off.

Severely Defected Surface: Repair large cracks and holes in your walls with sand and cement mixture and allow them to dry thoroughly. Scuff to make your walls smooth and dust off thoroughly.



Recommended Paint System

Type of Substrate: FOR MASONRY

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100/5200 WALL SEALER	1	
Putty	NIPPON WALL PUTTY	2-3	
Finish	NIPPON MATEX GOLD	3-4	

Standard Packing	:	Colour Creations Bases	•	0.91L, 3.64L, 14.56L
		Ready Mix	:	0.91L, 3.64L, 14.56L

Safety, Health and Environmental Information

Keep the paint out of reach of children and away from eatable items. Wear a mask and protective clothing while applying the paint. Do not discharge into drains or in an open environment.

Our paint is free of Lead, Mercury, Chromium, and Cadmium compounds.

Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control many conditions under which our products may be used, we can only guarantee the quality of the product.