



NIPPON ODOUR-LESS AIRCARE (Premium Interior Emulsion)

Recommended Uses

You can utilize Matex Pro for decoration and protection of interior walls, ceilings, plaster, brickwork, and wall boards.

Composition

- Pigments** : Mainly Titanium Dioxide, Iron Oxide, Organic Pigments and Mineral Extender.
- Binder** : Acrylic Polymer
- Thinner** : Clean Water

Application Methods

Thinning by Volume

- 1) Brush** : Dilute the paint with 20-30% water
- 2) Conventional Air Spray** : Dilute the paint with 30-40% water

Product Description

This breakthrough product contains Anti-Formaldehyde with Active Carbon Technology that continually absorbs harmful free formaldehyde from the air and converts it into water vapor, resulting in clean fresh air. Besides having low VOCs and odor, this environmentally friendly paint has superior washable properties, and anti-fungal properties and does not contain lead and mercury. It is ideal for people who are allergic to formaldehyde and paint odour. Hence it is recommended to be used in eco-sensitive commercial and residential areas such as hospitals, schools, hotels and homes.



- Clean Up** : Clean up your equipment with water immediately after use.
- Note** : Do not keep diluted paint for more than 1 day. If kept for longer periods it can lead to paint infection, color change and loss of viscosity.

Surface Preparation

Bare Masonry

For Bare Masonry surfaces make sure your walls should be completely dry and free from dust, dirt, and grease. Apply NIPPON VINILEX 5100 WALL SEALER and allow it to dry thoroughly. Sand and dust off your walls and make them smooth by applying 2-3 coats of NIPPON ACS PUTTY. Avoid painting when the moisture content and alkalinity of the walls are high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

Previously Painted Surfaces

Sound Surface: Make your surface sound by removing unstable paint film, and lose chalk by rubbing down using abrasive paper or wire brush and dusting off. Prime your walls with NIPPON VINILEX 5100 WALL SEALER. You can fill the surface of your walls with NIPPON ACS PUTTY if necessary.

Severely Defected Surface: Masonry work is recommended to repair large cracks and holes. Allow drying thoroughly. Prime your walls with NIPPON VINILEX 5100 WALL SEALER and fill with NIPPON ACS PUTTY. Scuff to make it smooth and dust off.



Recommended Paint System

Type of Substrate:
FOR MASONRY

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON ACS PUTTY	2-3	
Finish	NIPPON ODOUR-LESS AIRCARE	3-4	

Standard Packing : Colour Creations Bases: 1L, 4L, 16L

Safety, Health and Environmental Information

Keep the paint out of reach of children and away from eatable items. Wear a mask and protective clothing while applying the paint. Do not discharge into drains or in an open environment.

Our paint is free of Lead, Mercury, Chromium, and Cadmium compounds.

Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control many conditions under which our products may be used, we can only guarantee the quality of the product.