



NIPPON SATIN GLO MATT ENAMEL

Interior Emulsion

Recommended Uses

It is highly recommended for the decoration and protection of interior walls, wood, and matter.

Composition

- Pigments** : Mainly contain Titanium Dioxide, Iron Oxide, Organic Pigments, and Mineral Extender.
- Binder** : Acrylic Copolymer Emulsion.
- Thinner** : Clean Water

Application Methods

Thinning by Volume

- 1) Brush/Roller** : Dilute 10-15% with White Spirit or Mineral Turpentine.
- 2) Conventional Air Spray** : Dilute 15-20% with White Spirit or Mineral Turpentine.

Product Description

Nippon Satin Glo Matt Enamel is superior quality matt enamel with a satin sheen finish. With Excellent flow and leveling properties, it forms a smooth and durable finish. Because of its good stain-resistant property, it is recommended for application on interior wood, metal and wall surfaces.



Clean Up : Clean up equipment with White Spirit or Mineral Turpentin immediately after use.

Surface Preparation

New Surfaces

WOOD: Wood must be dry and free from dirt, grease and other contaminants. Smoothen the surface with sandpaper. Clean off and dry.

METAL: Surface must be dry and free from dirt, grease and other contaminants. Ferrous substrate should be sanded or wire-brushed to remove mill scales and rust. Clean off and dry.

WALL: Bare masonry surfaces should be completely dry and free from dust, dirt and grease. Use a bleach solution to treat the surface affected by fungus. Apply NIPPON VINILEX 5100 WALL SEALER and allow thorough drying. Sand and dust off. Smoothen the surface by applying 2-3 coats of NIPPON ACS PUTTY. Sand and dust off thoroughly.

Previously Painted Surfaces

WOOD, METAL & WALL:

Any loose and flaking paint film must be scraped off. Defective areas should be sanded and smoothened. For ferrous substrates, rust should be removed thoroughly. The entire surface must finally be dry and free from dirt, grease and other contaminants. The scraped areas should be primed prior to painting.



Recommended Paint System

Type of Substrate:
FOR WOOD

Sequence	Product Name	No. of Coats	Remarks
Primer	NIPPON 9000 ALUMINIUM WOOD PRIMER	1	
Undercoat	NIPPON 9000 UNDERCOAT / ECONOMY UNDERCOAT	1	
Finish	NIPPON SATIN GLO MATT ENAMEL	2-3	

FOR STEEL AND IRON

Sequence	Product Name	No. of Coats	Remarks
Primer	NIPPON RED OXIDE PRIMER / NIPPON ZINC CHROMATE PRIMER	1	
Undercoat	NIPPON 9000 UNDERCOAT / ECONOMY UNDERCOAT	1	
Finish	NIPPON SATIN GLO MATT ENAMEL	2-3	

MASONRY SURFACE

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON ACS PUTTY	2-3	
Finish	NIPPON SATIN GLO MATT ENAMEL	2-3	

Standard Packing : 0.91L and 3.64L

Safety, Health and Environmental Information

Keep the paint out of reach of children and away from eatable items. Wear a mask and protective clothing while applying the paint. Do not discharge into drains or in an open environment.

Our paint is free of Lead, Mercury, Chromium, and Cadmium compounds.

Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control many conditions under which our products may be used, we can only guarantee the quality of the product.