



NIPPON BRILLIANCE MATT ENAMEL

Premium Interior Enamel

Recommended Uses

For decoration and protection of interior walls, wood and metal.

Composition

Pigments : Mainly Titanium Dioxide, Iron Oxides, Carbon Black, Organic Pigments.
Soya Bean Oil modified Long Oil Alkyd

Binder : White Spirit or Mineral Turpentine

Application Methods

Thinning by Volume

1) Brush/Roller : Dilute 10-15% with White Spirit or Mineral Turpentine.

2) Conventional Air Spray : Dilute 15-20% with White Spirit or Mineral Turpentine.

Product Description

Nippon Brilliance Matt Enamel is an anti-fungal enamel of premium quality. It is recommended for interior walls, wood and metal. Easy to apply, this paint forms a luxurious smooth matt finish that is highly washable. With excellent stain-resisting properties it is extremely suitable for kitchens, bathrooms, corridors and staircases.



Clean Up: Clean up equipment with White Spirit or Mineral Turpentine immediately after use.

Note : Do not keep diluted paint for more than 1 day. If kept for longer periods it can lead to paint infection, color change and loss of viscosity.

Surface Preparation

New Surfaces

WOOD: Wood must be dry and free from dirt, grease, and other contaminants. Smoothen the surface with sandpaper. Clean off and dry.

METAL: The surface must be dry and free from dirt, grease, and other contaminants. Ferrous substrate should be sanded or wire-brushed to remove mill scales and rust. Clean off and dry.

WALL: Bare masonry surfaces should be completely dry and free from dust, dirt and grease. Use a bleach solution to treat the surface affected by fungus. Apply NIPPON VINILEX 5100 WALL SEALER and allow thorough drying. Sand and dust off. Smoothen the surface by applying 2-3 coats of NIPPON ACS PUTTY. Sand and dust off thoroughly.

Previously Painted Surfaces

WOOD, METAL & WALL: Any loose and flaking paint film must be scraped off. Defective areas should be sanded and smoothened. For ferrous substrates, rust should be removed thoroughly. The entire surface must finally be dry and free from dirt, grease, and other contaminants. The scraped areas should be primed before painting.



Recommended Paint System

Type of Substrate:
FOR WOOD

Sequence	Product Name	No. of Coats	Remarks
Primer	NIPPON 9000 ALUMINIUM WOOD PRIMER	1	
Undercoat	NIPPON 9000 UNDERCOAT / ECONOMY UNDERCOAT	1	
Finish	NIPPON BRILLIANCE MATT ENAMEL	2-3	

FOR STEEL AND IRON

Sequence	Product Name	No. of Coats	Remarks
Primer	NIPPON RED OXIDE PRIMER / NIPPON ZINC CHROMATE PRIMER	1	
Undercoat	NIPPON 9000 UNDERCOAT / ECONOMY UNDERCOAT	1	
Finish	NIPPON BRILLIANCE MATT ENAMEL	2-3	

MASONRY SURFACE

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON ACS PUTTY	2-3	
Finish	NIPPON BRILLIANCE MATT ENAMEL	3-4	

Standard Packing : Colour Creations: 0.91L & 3.64 L
Ready Mix : 0.91L & 3.64 L

Safety, Health and Environmental Information

Flammable. Keep away from sources of ignition and fire. Keep out of reach of children and away from food and drink. Harmful by inhalation and if swallowed. If swallowed seek medical advice immediately. Ensure good ventilation during application and drying. Do not breathe in vapor or sanding dust. Avoid contact with eyes and skin. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Wear protective clothing and a mask while applying the paint. Use soap and water to clean the splashes from the skin. Paint must always be stored in a cool and dry place. Care must be taken while transporting the paint. Always keep the container in a secure upright position. Use sand to contain any spillage. Dispose off paint by the appropriate the Environmental Quality Regulations. Do not discharge into drains or the environment. Chemical Safety Data Sheet available on request.

Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.