



NIPPON PAINT TIMBER FINISH WOOD SEALER

Recommended Uses

For decoration and protection of both interior and exterior Wood.

Composition

- Binder** : Plasticised nitrocellulose
Thinner : Nippon Paint Timber Finish Thinner

Product Description


Nippon Timber Finish Wood Sealer is an excellent Quick-drying wood Sealer which penetrates the pores of wood and seals the wood surface. After sanding provides smooth surface for topcoat application and also prevents sinkage of topcoat.

Application Methods

- Conventional Air Spray** : Thinning by Volume
In one part Nippon Timber Finish Wood Sealer use 1.5-2.0 parts Nippon Timber Finish Thinner.



Properties:



Colour
Milky



Appearance
Slightly Sheen



Recommended no. of coats
2 coats

Clean Up : Clean up equipment with Nippon Timber Finish Thinner immediately after use.

Specific Gravity : 0.96-0.98

Solid Content : 42+-3% by volume

Surface Preparation

Ensure that the wood is dried right through and properly seasoned. Thoroughly scuff the bare wood with a coarse abrasive paper to produce a uniform surface. Level out all the surface pits and imperfections properly with a mechanical sander.

Application Preparation:

Spray two coats of Nippon Paint Timber Finish Wood Sealer after thinning with Nippon Timber Finish Thinner. Allow to dry for 2 hours before scuffing and Over-coating with Nippon Timber Finish Wood Clear or Matt Lacquer.



Recommended Paint System

Type of Substrate:

Properly seasoned, dry and thoroughly scuffed wood

| Sequence | Product Name | No. of Coats | Remarks |
|------------------|--|--------------|---------|
| Sealer Finish | Nippon Paint Timber Finish Wood Sealer | 2-3 | |
| | Nippon Paint Timber Finish Matt Lacquer | 2-3 | |

Standard Packing :

Safety, Health and Environmental Information

Keep out of reach of children and away from food and drink. Do not swallow the paint. If swallowed seek medical advice immediately. Ensure good ventilation during application and drying. Do not breathe in vapor or sanding dust. Avoid contact with eyes and skin. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Wear protective clothing and mask while applying the paint. Use soap and water to clean the splashes from skin. It is a highly flammable material. All sources of ignition must be eliminated in, or near the working place. Paint must always be stored in a cool and dry place. Care must be taken while transporting the paint. Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of paint in accordance with the appropriate Environmental Quality Regulations. Do not discharge into drains or environment. Chemical Safety Data Sheet available on request.

Does not contain any added Lead, Mercury, Chromium and Cadmium Compounds.

Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given data without prior notice.