

## NIPPON QUALITY EMULSION

Interior Paint

### Recommended Uses

You can use Nippon Quality Emulsion for decorating and protecting your interior walls, ceilings, plaster, brickwork, and wall boards.

### Composition

- Pigments** : Mainly Titanium Dioxide, Iron Oxide, Organic Pigments and Mineral Extender.
- Binder** : Modified Acrylic Emulsion
- Thinner** : Clean Water

### Application Methods

Thinning by Volume

- 1) Brush** : Dilute the paint with 50-70% water
- 2) Roller** : Dilute the paint with 20-30% water
- 3) Conventional Air Spray** : Dilute the paint with 30-40% water

### Product Description

Nippon Quality Emulsion is a styrene acrylic based emulsion with smooth flat finish designed for interior concrete surfaces including walls and ceilings. It gives your walls a good hiding and covering with a wide range of long-lasting colours.



**Clean Up :** Clean up your equipment with water immediately after use.

## Surface Preparation

### Bare Masonry

For Bare masonry surfaces make sure it should be completely dry and free from dust, dirt, and grease. Sand and dust off your walls thoroughly.. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls is still high.

(Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9 ).

## Previously Painted Surfaces

### Sound Surface:

Remove unstable paint film, loose chalk by rubbing down using abrasive paper or wire brush and dust off. Prime with NIPPON 5200 PRIMER. Fill the surface with NIPPON PUTTY if necessary.

### Severely Defected Surface:

Use sand and cement mixture to repair large cracks and holes and allow thorough drying. Prime with NIPPON 5200 primer. Fill with NIPPON PUTTY. Scuff to make smooth and dust off thoroughly.



## Recommended Paint System

**Type of Substrate:**  
FOR MASONRY

| Sequence | Product Name  | No. of Coats | Remarks |
|----------|---|--------------|---------|
| Sealer   | NIPPON 5200 PRIMER  | 1            |         |
| Putty    | NIPPON A-100/ PVA WALL PUTTY  | 2-3          |         |
| Finish   | NIPPON QUALITY EMULSION   | 3-4          |         |
| Note:    | It can be applied directly to ceilings where the coating is a major factor. |              |         |

**Standard Packing** : 0.91lit, 3.64 lit, 14.56lit (Ready Mix)

## Safety, Health and Environmental Information

Keep the paint out of reach of children and away from eatable items. Wear a mask and protective clothing while applying the paint. Do not discharge into drains or in an open environment.

Our paint is free of Lead, Mercury, Chromium, and Cadmium compounds.

## Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control many conditions under which our products may be used, we can only guarantee the quality of the product.