



## SUPER MATEX

Interior Emulsion

### Recommended Uses

For decoration and protection of interior walls, ceilings, plaster, brickwork and wall boards.

### Composition

- Pigments** : Mainly Titanium Dioxide, Iron Oxide, Organic Pigments and Mineral Extender.
- Binder** : Vinyl Acrylic Copolymer Emulsion.
- Thinner** : Clean Water

### Application Methods

Thinning by Volume

- 1) Brush** : Dilute the paint with 50-70% water
- 2) Roller** : Dilute the paint with 20-30% water
- 3) Conventional Air Spray** : Dilute the paint with 30-40% water

### Product Description

Nippon Super Matex Emulsion with its unique anti-fungal and easy-to-wash properties is the best value for money. It is specially formulated to provide a smooth finish for interior walls, ceilings, plaster, brickwork, and wall boards. Good brushing, hiding, and excellent adhesion make the paint film last for a long.



- Clean Up :** Clean up your equipment with water immediately after use.
- Note :** Do not keep diluted paint for more than 1 day. If kept for longer periods it can lead to paint infection, color change and loss of viscosity.

## Surface Preparation

Bare masonry surfaces should be completely dry and free from dust, dirt, and grease. Use a Bleach solution to treat the surface affected by fungus. Apply NIPPON VINILEX 5100 WALL SEALER and allow thorough drying. Smoothen the surface by applying NIPPON ACS PUTTY. Sand and dust off thoroughly. Allow all surfaces to dry completely before painting. Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

## Previously Painted Surfaces

**Sound Surface:** Remove unstable paint film, and loose chalk by rubbing down using abrasive paper or wire brush and dust off. Prime with NIPPON VINILEX 5100 WALL SEALER. Fill the surface with NIPPON ACS PUTTY if necessary.

**Severely Defected Surface:** Use sand and cement mixture to repair large cracks and holes and allow thorough drying. Prime with NIPPON VINILEX 5100 WALL SEALER. Fill with NIPPON ACS PUTTY. Scuff to it make smooth and dust off thoroughly.



## Recommended Paint System

**Type of Substrate:**  
FOR MASONRY

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON ACS PUTTY	2-3	
Finish	NIPPON SUPER MATEX	3-4	

**Standard Packing** : 3.64L, 14.56L

## Safety, Health, and Environmental Information

Keep out of reach of children and away from food and drink. Do not swallow the paint. If swallowed seek medical advice immediately. Ensure good ventilation during application and drying. Do not breathe in vapor or sanding dust. Avoid contact with eyes and skin. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Wear protective clothing and a mask while applying the paint. Use soap and water to clean the splashes from the skin. Paint must always be stored in a cool and dry place. Care must be taken while transporting the paint. Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of paint in accordance with the appropriate the Environmental Quality Regulations. Do not discharge into drains or environment. Does not contain any added Lead, Mercury, Chromium, and Cadmium compounds.

## Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice.