



## NIPPON PAINT TIMBER FINISH MATT LACQUER

### Recommended Uses

For decoration and protection of both interior and exterior Wood.

### Composition

**Pigments** : Mainly Titanium Dioxide, Iron Oxides, Carbon Black, Organic Pigments.

**Binder** : Plasticised nitrocellulose

**Thinner** : Nippon Paint Timber Finish Thinner

### Application Methods

**Conventional Air Spray** : Thinning by Volume  
In one part Nippon Timber Finish Matt Lacquer uses 1.5-2.0 parts Nippon Timber Finish Thinner.

### Product Description

Nippon Timber Finish Matt Lacquer is a premium quality topcoat NC Matt Lacquer for sealed wood surfaces which provides hard, scratchproof and matt Finish. Good flexibility gives long life performance without cracking. Also Provides excellent resistance to water, tea and beverage stains.



### Properties:



**Colour**  
Milky



**Appearance**  
Matt



**Recommended no. of coats**  
2-3 coats

### Coverage

12-13 m<sup>2</sup> per litre per coat  
(Coverage may vary depending on the substrate conditions)



### Drying Time

**Touch Dry:**  
15-20 minutes  
**Hard Dry:**  
04 hours



### Recoating Interval

30 minutes



**Clean Up** : Clean up equipment with Nippon Timber Finish Thinner immediately after use.

**Specific Gravity** : 0.94-0.96

**Solid Content** : 41+-3% by volume

## Surface Preparation

Ensure that the wood is dry right through and properly seasoned. Thoroughly scuff the bare wood with a coarse abrasive paper to produce a uniform surface. Level out all the surface pits and imperfections properly with a mechanical sander. Seal the wood surface with Nippon Paint Timber Finish Wood Sealer. Scuff to make it smooth and dust off thoroughly.

## Application Preparation:

Spray two coats of Nippon Paint Timber Finish Matt Lacquer after thinning with Nippon Timber Finish Thinner. Air dry for 3 – 4 hours and wet scuff using white spirit and 400-grade paper. Wipe dry and spray third coat. Allow it to dry overnight.



## Recommended Paint System

### Type of Substrate:

Properly seasoned, dry and thoroughly scuffed wood

Sequence	Product Name	No. of Coats	Remarks
Sealer Finish	Nippon Paint Timber Finish Wood Sealer	2-3	
	Nippon Paint Timber Finish Matt Lacquer	2-3	

**Standard Packing** :

## Safety, Health and Environmental Information

Keep out of reach of children and away from food and drink. Do not swallow the paint. If swallowed seek medical advice immediately. Ensure good ventilation during application and drying. Do not breathe in vapor or sanding dust. Avoid contact with eyes and skin. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Wear protective clothing and mask while applying the paint. Use soap and water to clean the splashes from skin. It is a highly flammable material. All sources of ignition must be eliminated in, or near the working place. Paint must always be stored in a cool and dry place. Care must be taken while transporting the paint. Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of paint in accordance with the appropriate Environmental Quality Regulations. Do not discharge into drains or environment. Chemical Safety Data Sheet available on request.

Does not contain any added Lead, Mercury, Chromium and Cadmium Compounds.

## Note

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given data without prior notice.