



NIPPON GLAMOUR

Interior Paint

Product Description:

Nippon Glamour is a premium quality water based matt formulated on specialized Acrylic binder modified with silicone additives and specially designed to give a luxurious smooth silky finish to interior masonry surfaces, brickworks & wallboards. It is a highly washable emulsion with added fresh lemon fragrance. Its fungus resistance properties, smooth silky finish and long lasting colors make it a flawless choice for interiors.

Recommended Uses:

For decoration and protection of interior walls, ceilings, plaster, brickwork, and wall boards.

Composition:

| | |
|-----------------|---|
| Pigments | : Mainly Titanium Dioxide, Iron Oxide, Carbon Black and Organic Pigments and Mineral Extender |
| Binder | : Acrylic Polymer |
| Thinner | : Clean Water |

Properties:

| | |
|-------------------------|--|
| Color Appearance | : A wide range of colours. Please refer to color card. : Soft Sheen |
|-------------------------|--|

| | |
|--|--|
| Recommended no. of coats | : 3-4 coats |
| Recommended Dry Film Thickness Per Coat | : 30 - 40 μ m |
| Drying Time | |
| Touch Dry | : Minimum 30 minutes.(Dependent on temperature and humidity) |
| Hard Dry | : 1 Hour |
| Recoating Interval | : 2-3 Hours |
| Theoretical Coverage | : 10- 12 m ² per litre per coat (Coverage may vary depending on the substrate conditions.) |

Application Methods:**Application Tool****Thinning By Volume**

- | | |
|---------------------------|---------------------------------------|
| 1) Brush | : Dilute the paint with 50-70% water. |
| 2) Roller | : Dilute the paint with 20-30% water. |
| 3) Conventional Air Spray | : Dilute the paint with 30-40% water. |

Surface Preparation:**Bare Masonry**

Bare masonry surfaces should be completely dry and free from dust, dirt and grease. Use a Bleach solution to treat the surface affected by fungus. Apply NIPPON VINILEX 5100 WALL SEALER and allow thorough drying. Sand and dust off. Smoothen the surface by applying 2-3 coats of NIPPON ACS PUTTY. Sand and dust off thoroughly. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls is still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

Previously Painted Surfaces**Sound Surface:**

Remove unstable paint film, loose chalk by rubbing down using abrasive paper or wire brush and dust off. Prime with NIPPON VINILEX 5100 WALL SEALER. Fill the surface with NIPPON ACS PUTTY if necessary.

Severely Defected Surface:

Masonry work is recommended to repair large cracks and holes. Allow to dry thoroughly. Prime with NIPPON VINILEX 5100 WALL SEALER. Fill with NIPPON ACS PUTTY. Scuff to make smooth and dust off thoroughly.

Recommended Paint System**Type of Substrate:**

FOR MASONRY

| Sequence | Product Name | No. of Coats |
|----------|---------------------------------|--------------|
| Sealer | NIPPON VINILEX 5100 WALL SEALER | 1 |
| Putty | NIPPON ACS PUTTY | 2-3 |
| Finish | NIPPON GLAMOUR | 3-4 |

Standard Packing : 1L, 4L & 16 L

Safety, Health and Environmental Information:

Keep out of reach of children and away from food and drink. Do not swallow the paint. If swallowed seek medical advice immediately. Ensure good ventilation during application and drying. Do not breathe in vapor or sanding dust. Avoid contact with eyes and skin. When applying paint it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Wear protective clothing and mask while applying the paint. Use soap and water to clean the splashes from skin. Paint must always be stored in a cool and dry place. Care must be taken while transporting the paint. Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of paint in accordance with the appropriate Environmental Quality Regulations. Do not discharge into drains or environment. Chemical Safety Data Sheet available on request.

Does not contain any added Lead, Mercury, Chromium and Cadmium compounds.

Note:

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given data without prior notice.